

[seal]

UNION OF SOVIET
SOCIALIST
REPUBLICS

(19) SU (11) 1441051 A2
(51) 4 E 21 B 10/16

USSR STATE COMMITTEE
ON INVENTIONS AND DISCOVERIES

DESCRIPTION OF INVENTION

ATTACHMENT TO CERTIFICATE OF AUTHORSHIP

[stamp: illegible]

(61) 1263799

(21) 4233447/22-03

(22) Jan. 26, 1987

(46) Nov. 30, 1988 Bull. No. 44

(71) Special Design Bureau for Drill Bits of the
Kuibyshevburmash Production Association


(72) Yu. V. Karpukhin, R. Yu. Kondrashov,
V. N. Gladkikh, A. V. Torgashov,
A. A. Loginov, A. V. Bykov, N. M. Garanin,
V. A. Korotayev, I. N. Tokarev,
R. S. Mustakhimov, V. P. Budin,
S. I. Makarov, and U. N. Yakimchuk

(53) 622.24.051.55 (088.8)

(56) USSR Certificate of Authorship
No. 1263799, cl. E 21 B 10/16, 1983.

(54) DRILL BIT CUTTER

(57) The invention relates to drilling. The purpose of the invention is to increase the efficiency of drilling. The cutter contains rows of teeth that are grouped in semicircles (1-4) by increment of spacing. The teeth in each group of the row are oriented opposite at a 15-45 angle to the cutter. Groups of teeth with a larger increment alternate with groups of teeth with a smaller increment on the adjacent row. The teeth of adjacent rows are oriented opposite to each other along the cutter. When the cutter is working, the cusps between the indentations on the face from the teeth of one semicircle are covered by the teeth of the other semicircle. This promotes destruction of the rod on the face. 1 z.p. formula, 1 ill.



(19) SU (11) 1441051 A2

1

The invention relates to rock drilling bits and is an improvement of the existing device under certificate of authorship No. 1263799.

The purpose of the invention is to increase the efficiency of drilling.

The drawing shows the proposed cutter from above.

On the rows of one semicircle (1 and 2), the teeth are placed at the angle α_1 or β_1 to the cutter, and on the other semicircle (3 and 4) at the angle α_2 or β_2 and are inclined in opposite directions with respect to the cutter. Teeth grouped with an interval of t_1 and t_2 alternate with teeth grouped with an interval of t_3 and t_4 , respectively; $t_1 > t_3$ and $t_4 > t_2$. The teeth inclined at α_1 and α_2 on one row alternate with the teeth inclined at the angle β_1 and β_2 , respectively, on the adjacent row.

The cutter works in the following manner.

When the cutter rotates, there is a reduction in wear and partial chipping of the tips of the main cutting edges, because the cusps between

2

the indentations on the face from the teeth of one semicircle are covered by the teeth of the other semicircle.

The proposed scheme of placement of teeth on the cutter permits an increase in the rate of drilling and the mechanical speed of drilling due to the destruction of the rod on the face and enhances the durability of the rig by more evenly distributing the load along the cutter.

Formula of the Invention

1. A drill bit cutter under certificate of authorship No. 1263799, *distinguished* by the fact that, in order to increase the efficiency of drilling, teeth in each group of the row are oriented opposite at a 15–45 angle to the cutter. Groups of teeth with a larger increment alternate with groups of teeth with a smaller increment on the adjacent row.

2. A drill bit cutter as in 1, *distinguished* by the fact that the teeth of adjacent rows are oriented along the cutter in directions opposite to each other.

Prepared by Yu. Palashchenko

Editor T. Parfenova

Technical editor I. Veres

Proofreader L. Patai

Order 6105/35

532 copies

Subscription

All-Union Scientific Research Institute for Patent Information of the USSR State Committee on Inventions and Discoveries

4/5 Raushskaya Embankment, Zh-35, Moscow 113035

Printing and Production Enterprise, 4 Proyektnaya St., City of Uzhgorod